In the Claims:

Please consider the following claims:

(Original) A fish luring system for luring fish to a lure attached to an end of a fishing line, said system comprising:

a fishing pole having a rod portion and a handle portion, said rod portion having a first end and a second end, said second end of said rod portion having a channel extending into said rod portion, said channel extending along a longitudinal axis of said rod portion;

said handle portion being mounted on said second end of said rod portion, said handle portion having an interior with an open end extending into said interior of said handle portion;

said interior of said handle being in communication with said channel extending through said rod portion of said fishing pole;

a protruding member for selectively supporting a finger of a user, said protruding member extending away from a peripheral wall of said handle portion;

said protruding member having a width tapering from said handle portion toward an end of said protruding member;

a cap for selectively closing said open end of said handle portion, said cap having an inner surface;

2

said inner surface of said cap being threadedly coupled to an outer surface of said handle portion adjacent to said open end of said handle portion;

a plurality of eyelets being mounted on said rod portion, each of said eyelets being spaced apart from each other, each of said eyelet being in registration with each of the other;

a vibrating assembly for vibrating said fishing pole, said vibrating assembly including:

a motor adapted for rotational movement, said motor being mounted in said interior of said handle portion;

a motor shaft being rotatably coupled to and extending from said motor toward said first end of said rod portion, said motor shaft being elongated and positioned in said channel in said rod portion;

said motor shaft comprising a substantially rigid material;

a cam being formed on an end of said motor shaft for selectively engaging an inner surface of said channel of said rod portion of said fishing pole;

said end of said motor shaft mounted on said cam being positioned generally adjacent to a central portion of said cam such that said cam travels in an eccentric circle when rotated by said motor shaft, wherein said cam selectively engages said inner surface of said channel

ont.

in said rod portion of said fishing rod, wherein said cam causes said first end of said rod portion to vibrate, wherein vibration of said first end of said rod portion vibrates the fishing line and an attached lure;

said cam comprising a substantially rigid material;

a power supply for selectively providing power to said motor, said power supply being mounted in said interior of said handle portion, said power supply being electrically connected to said motor;

a biasing member for selectively biasing said power supply away from an interior of said cap, said biasing member being attached to a bottom surface of said cap and positioned generally between said cap and said power supply; and

a switch for selectively controlling said motor, said switch being depressibly mounted on said protruding portion, said switch being electrically connected to said motor.

21. (New) A fishing pole, comprising:

a rod portion;

a handle portion having a hollow interior space;

Δ

Dallasz 987453 v 1, 62495,00003USPT

a vibrating assembly mounted within the hollow interior space of the handle portion which, when activated, causes vibration to be initiated within the handle portion.

(New) The fishing pole of claim 21 wherein the vibrating ssembly comprises:

a motor having a rotating shaft; and

an eccentric member mounted to, and rotated by, the shaft to effectuate the vibration which is initiated within the handle portion.

- (New) The fishing pole of claim 22 wherein the eccentric 23. member comprises a cam.
- (New) The fishing pole of claim 21 further including an 24. actuating means associated with the handle portion for actuating the vibrating assembly.

(New) A handle for a fishing pole, comprising: a hollow interior space within the handle;

Dallas2 987453 v 1, 62495,00003USPT

a vibrating assembly mounted within the hollow interior space of the handle portion which, when activated, causes vibration to be initiated within the handle itself.

26. (New) The handle of claim 25 wherein the vibrating assembly comprises:

a motor having a rotating shaft; and

an eccentric member mounted to, and rotated by, the shaft to effectuate the vibration within the handle.

- 27. (New) The handle of claim 26 wherein the eccentric member comprises a cam.
- New) The handle of claim 25 further including an actuating means associated with the handle for actuating the vibrating assembly.
 - 29. (New) A fishing pole, comprising:
 - a rod portion having an axially extending hollow cavity;
 - a handle portion having a hollow interior space; and
 - a vibrating assembly comprising:

6

10 read

a motor mounted within the hollow interior space of the handle portion, the motor having a rotating shaft which extends into the hollow cavity of the rod portion; and

an eccentric member mounted to the shaft at a position within the hollow cavity, the eccentric member being rotated by the shaft to cause vibration to be initiates within the rod portion.

- 30. (New) The fishing pole of claim 29 wherein the shaft portion has a distal end, the rotating shaft extending proximate to the distal end, the eccentric member mounted to the shaft at a position within the hollow cavity proximate to the distal end to cause vibration to be initiated at the distal end of the rod portion.
- 31. (New) The fishing pole of claim 29 wherein the eccentric member comprises a cam.
 - 32. (New) The fishing pole of claim 29 further including an actuating means associated with the handle portion for actuating the vibrating assembly.

33. (New) The fishing pole of claim 29 wherein the eccentric member engages an interior surface of the hollow cavity of the rod portion to induce vibratory movement of the rod portion.

Fax: 214-855

(New) The fishing pole of claim 33 wherein the shaft portion has a distal end, the rotating shaft extending proximate to the distal end, the eccentric member mounted to the shaft at a position within the hollow cavity proximate to the distal end, and the eccentric member engaging the interior surface of the hollow cavity of the rod portion proximate the distal end to cause vibration to be initiated at the distal end of the rod portion.

- A vibrating accessory for use with a fishing pole, mprising:
 - a housing having a hollow interior space;
- a vibrating assembly mounted within the hollow interior space of the housing which, when activated, caused vibration to be initiated within the housing itself; and

mounting means for attaching the housing to a selected location of the fishing pole for transferring the initiated vibration to the fishing pole.

Dallas2 987433 v 1, 62495.00003USPT

11

PATENT APPLICATION
Docket No. 62495-3uspt

36. (New) The accessory of claim 35 wherein the vibrating assembly comprises:

a motor having a rotating shaft; and

an eccentric member mounted to, and rotated by, the shaft to effectuate the vibration initiated within the housing.

37. (New) The accessory of claim 35 wherein the eccentric member comprises a cam.

38. (New) The accessory of claim 35 further including an actuating means which is associated with a handle portion of the fishing pole to which the housing is attached for actuating the vibrating assembly.

 λ^{39} . (New) A fish luring system, comprising:

portion having a first end and a second end and a longitudinally extending channel, said handle portion being mounted to said second end of said rod portion, said handle portion having an interior space in communication with said longitudinally extending channel;

Dellas2 987453 v 1, 62495.00003USPT

a plurality of spaced-apart eyelets being mounted on said rod portion;

a vibrating assembly comprising:

a motor adapted for rotational movement, said motor being mounted in said interior space of said handle portion;

a shaft being rotatably coupled to and extending from said motor;

an eccentric member mounted to said shaft for vibratory rotation within said fishing pole;

a power supply for selectively providing power to said motor, said power supply being mounted in said interior space of said handle portion, said power supply being electrically connected to said motor; and

a switch for selectively controlling said motor.

40. (New) The system of claim 39 wherein the eccentric member is

positioned within the interior space of the handle portion to cause vibration which initiates within the handle portion.

(New) The system of claim 39 wherein the eccentric member is 41. positioned within the longitudinally extending channel of the rod portion to cause vibration which initiates within the rod portion.

(New) The system of claim 41 wherein the eccentric member is 42. positioned within the longitudinally extending channel proximate to the first end of the rod portion to cause vibration which initiates within the rod portion at the first end.